



EVA SHOE INJECTION MOULDING MACHINE

CATALOGUE

www.starlinkmachinery.com

Mail to: sales@starlink.cc

EVA SHOE INJECTION MOULDING MACHINE



➤ INFORMATION

1. Adopt design of larger die holder, produce more in the same time, which increasing the productivity a lot.
2. The error between two mold can be automatic compensated.
3. The injection oil hydraulic system adopts the proportional flow pressure control valve
4. The injection part controlled by 5-stage PID, achieve the setting temperature fast and steadily to insure the high quality of completed products
5. Adopt the function of auto diagnosis and maintain to operate the monitor system, where the machine status shown.
6. Controlled and operated by the touch screen PLC.

➤ SPECIFICATIONS

<i>Work Stations</i>	<i>6 stations</i>
<i>Clamping Force</i>	<i>180tons</i>
<i>Mould Space</i>	<i>285*520*2mm</i>
<i>Opening Stroke</i>	<i>340mm</i>
<i>Screw Diameter</i>	<i>60mm</i>
<i>Injection Capacity</i>	<i>600cc</i>
<i>Injection Pressure</i>	<i>1000kg/cm²</i>
<i>Injection Speed</i>	<i>10cm/sec</i>
<i>Screw rotate speed</i>	<i>0-185rpm</i>
<i>Temperature Control</i>	<i>4 point</i>
<i>Machine Dimension</i>	<i>7800*5000*2700mm</i>
<i>Machine Weight</i>	<i>26000kg</i>